



- saw frame swivels - allowing angular cuts to 45°
- coolant system is included
- thin saw blade for reduced material removal

Specifications

B 200 S

Cutting capacities

Cutting capacity 90° - round	mm	205
Cutting capacity 90° - square	mm	205
Cutting capacity 90° - flat	mm	205x215
Cutting capacity 45° (square) L	mm	115
Cutting capacity 45° (round) L	mm	135
Cutting capacity 45° (flat) L	mm	205x115
Belt speed	m/min	24 / 41 / 61 / 82

Drive capacity

Motor rating main drive	kW	1,1
Supply voltage	V	400

Measures and weights

Belt dimensions	mm	2.360x20x0,9
Overall dimensions (length x width x height)	m	1,23x0,65x1,32
Weight	kg	190
Part No.		102752



Minimum down-times: allows precise adjustment of angular stops, including quick-action clamps at the vise

- exact cuts - rigid construction prevents belt track deviations
- quiet, low-vibration operation
- saw frame feed is infinitely variable via hydraulic cylinder

Standard Equipment

coolant system, quick-action vice, mobile base, saw-band, operator manual

Bi-Metallic Band Saw Blades

for model	Dimensions	Teeth/inch	Part No.
B 200 S	2360 x 20 x 0.90	4/6	119 150