



HB 250 A is shown



HB 150 is shown



HB 210 A is shown

## Specifications

		HB 150	HB 210A	HB 250A
<b>Cutting Capacities</b>				
Cutting capacity 90° - round	mm	150	170	225
Cutting capacity 90° - flat	mm	120x200	140x200	245x190
Cutting capacity 60° - round	mm	-	-	90
Cutting capacity 45° - flat	mm	90x130	95x130	210x155
Cutting capacity 45° - round	mm	120	125	155
Belt speed	m/min	40 / 80	40 / 80	40 / 90
<b>Drive Capacity</b>				
Motor rating main drive	kW	0,6	0,75	1,1
<b>Measures and Weights</b>				
Overall dimensions (l x w x h)	m	1,16x0,71x0,79	1,3x0,58x0,88	1,36x0,58x0,9
Weight	kg	212	152	185
Part No.		152822	152850	152796

- cast-iron saw frame, one-piece construction
- for miter cuts, the operator moves the saw frame - not the material
- Hydraulic cylinder provides for infinitely variable support pressure and saw frame feed
- vise with quick-action clamping feature

## Standard Equipment

1 saw blade, coolant system, base, quick-action vise, hydraulic cylinder for saw frame, operator manual

## Bi-metallic saw blades

for model	Dimensions in mm	Teeth/inch
<b>HB 150</b>	2060 x 20 x 0,90	4/6, 5/8
<b>HB 210 A</b>	2080 x 20 x 0,80	5/8, 10/14
<b>HB 250 A</b>	2480 x 27 x 0,90	5/8, 8/12